

1VLH10W-OD Outdoor-Rated, Water-Cooled Chiller/Heater

Specifications and Features

- Fluid Setpoint Range -70°C to +60°C
- Temperature Stability ± 0.5°C or better
- Net Cooling Capacities 3,000 Watts at -50°C
 375 Watts at -70°C
- Heating Capacity 3,000 Watts on 208 VAC
- Recirculating Flow/Pressure 4 Gpm at 30 Psi, 2 Gpm at 60 Psi
- Stainless Steel Reservoir 5 Gallons, Sealable
- Recirculating Fluid Golden ZT-100 or Syltherm HF
- Recirculating Supply/
 Return Fittings 3/4" Stainless Steel FPT
- Facilities Supply/
 Return Fittings 1/2" Stainless Steel FPT
- Facilities Requirements Up to 3.5 Gpm at 70°F inlet,
 20 Psi ΔP
- Electrical Service 208/230 VAC, 60 Hz, 3 phase,
 40 amp service
- Physical Parameters 68" H x 30" W x 50" D
 1,200 pounds dry weight
- Warranty 12 Months, Parts and Labor
- Refrigerant R-507, 15 lbs.
- Compressor 12 Hp semi-hermetically sealed
- Condenser A brazed plate heat exchanger is used and
 a refrigerant pressure actuated water flow
 control automatically adjusts water usage
- Pump Magnetic-drive turbine pump powered by a
 variable frequency drive (VFD) to provide
 adjustable output flow and pressure
- Safety Interlocks Reservoir low level and empty float switches,
 refrigerant high and low pressure switches,
 turbine fluid flowmeter, over-temp switch



Similar **Larger** Model Shown

- Controller PID type controller that utilizes
 fully proportional cooling and
 heating with the Mydax
 patented refrigeration circuit.
- Construction Welded steel frame with
 aluminum side panels. Frame
 and panels are powder coated
 for durability. Locking casters
 with adjustable leveling pads
 or I-beam supports.
- Interfacing RS-232 for Remote Control
 and Monitoring
- Safety Standards Refrigeration Standard ARI
 590-2, National Electrical Code
 NFPA-70, Electrical Standard
 for Industrial Machinery
 NFPA-79

Patents: #4,742,689, #4,959,972, #4,934,155



12260 Shale Ridge Lane
Auburn, CA 95602
530-888-6662

2008.08.06

Fax: 530-888-0962
www.mydax.com
E-mail: sales@mydax.com